

FIG. 1



FIG. 2B

FIG. 2C

FIG. 2D

FIG. 2E

FIG. 2A


SCANNING MEANS
950
(1) RECORDING BY LASER
LASER
(2) BARCODE
(3) REPRODUCED SIGNAL
t
FIRST SLICE LEVEL
SECOND SLICE LEVEL
(4) LOW-REFLECTIVITIY SIGNAL
0
0
1
T1
T2
T3
T4
T5
T6
t
(5) LOW-REFLECTIVITIY DETECTION SIGNAL
PE-RZ MODULATED SIGNAL DEMODULATOR
621
ENCRYPTED DATA OUTPUT

FIG. 3


FIRST DISK FABRICATION PROCESS
806
STEP (1)
FORMING
801
SPUTTERING
STEP (2)
REFLECTIVE
FILM FORMATION
802
801
ULTRAVIOLET RADIATION
803
804
STEP (3)
LAMINATION
AND HARDENING
PRINTED LAYER
805
803
804
STEP (4)
LABEL PRINTING
802
801
SECONDARY
RECORDING
PROCESS
805
803
804
STEP (5)
FORMATION
OF FIRST
OPTICAL
MARK
802
801
814
PULSED LASER
813
①

FIG. 4


1
PRINTED LAYER
805
803
STEP (6)
READING OR FIRST OPTICAL MARK
815
STEP (7)
WAVEFORM (a)
FIRST SLICE LEVEL
SECOND SLICE LEVEL
t
WAVEFORM (b)
MARKING DETECTION SIGNAL
0
1
0
t
SIGNAL (c)
SYNCHRONIZING REPRODUCED CLOCK
t
SIGNAL (d)
ADDRESS n
ADDRESS n + 1
(e)
ADDRESS n
FRAME SYNCHRONIZING SIGNAL (1)
FRAME SYNCHRONIZING SIGNAL (2)
FRAME SYNCHRONIZING SIGNAL (m)
REPRODUCED CLOCK (1)
REPRODUCED CLOCK (k)
REPRODUCED CLOCK (1)
REPRODUCED CLOCK (k)
REPRODUCED CLOCK (1)
REPRODUCED CLOCK (2)
REPRODUCED CLOCK (k)

FIG. 5


FORMING a (1a)
FORMING b (1b)
(2a)
SPUTTERING OF HIGH REFLECTIVITY FILM
(70% OR OVER: Al)
803
802
SPUTTERING
SPUTTERING
(2c)
SPUTTERING OF SEMI-TRANSPARENT REFLECTIVE FILM
(30% Au)
825
801
STEP (3)
LAMINATION
804
PRINTED LAYER
STEP (4)
LABEL PRINTED LAYER
STEP (5)
LASER TRIMMING
LASER

FIG. 6


PRINTED LAYER
815
(6) MARKING ON DISK
803
802
804
825
801
826
LASER
(7) WAVEFORM (FIRST LAYER)
FIRST SLICE LEVEL
SECOND SLICE LEVEL
t
(8) MARKING DETECTION SIGNAL (FIRST LAYER)
ADDRESS n1
0
1
0
(9) SYNCHRONIZING REPRODUCED CLOCK (FIRST LAYER)
ADDRESS n1
(10) WAVEFORM (SECOND LAYER)
FIRST SLICE LEVEL
SECOND SLICE LEVEL
(11) MARKING DETECTION SIGNAL (SECOND LAYER)
ADDRESS n1
0
1
0
(12) SYNCHRONIZING REPRODUCED CLOCK (SECOND LAYER)
ADDRESS n1

FIG. 7



FIG. 8A



FIG. 8B

FIG. 9A



FIG. 9B



FIG. 9C



FIG. 9D





FIG. 10A



FIG. 10B


Al
REGION WHERE ADHESIVE LAYER WAS FORMED
Al
0.05 μm
0.2 μm
0.2 μm
0.05 μm
PC (POLYCARBONATE SUBSTRATE)
1.8 μm
LOW-REFLECTIVITY PORTION 10 μm
1.9 μm
MAGNIFICATION: X 20,000

FIG. 11



FIG. 12A



FIG. 12B



FIG. 13A


MASTER DATA
A1 A2 A3 A4 A5 A6 A7 A8 A9
ILLEGALLY DUPLICATED CD
MARK NO. = 2
MARK NO. = 1
584x
Z1
Z2
Z3
Z4
A1 A2 A3 A4 A5 A6 A7 A8 A9 A10 A11 A12 A13 A14 A15 A16 A17 A18 A19 A20 A21 A22 A23
(POLAR COORDINATE-ADDRESS) PHYSICAL POSITION TABLE
ZONE | ADDRESS
Z1 |
Z2 | A6
Z3 | A4, A10
Z4 | A8
LOW-REFLECTIVITY PORTION ADDRESS TABLE
MARK NO. | ADDRESS | CLOCK COUNT
1 | A2 | 81
1 | A8 | 103
1 | A18 | 120
2 |
2 |
2 |
609x

FIG. 13B

FIG. 14A
FIG. 14B

FIG. 14C
FIG. 14D

FIG. 14



FIG. 14A

FIG. 14B

TYPICAL EQUATION
FOR EDC COMPUTATION
EDC (ERROR DETECTION CODE) :

$$EDC_{PCA}(x)=\sum_{i=0}^{31} bi \bullet x^{i}$$

$$I_{PCA}(x)=\sum_{i=32}^{128n-31} bi \bullet x^{i}$$

FIG. 14C

TYPICAL EQUATION
FOR EDC COMPUTATION
ECC (ERROR CORRECTION CODE) :

$$R_{PCA}(x)=\sum_{i=48}^{51} I_{j+4i} \bullet x^{51-i}$$

$$I_{PCA}(x)=\sum_{i=0}^{4n-2} I_{j+4i} \bullet x^{51-i}+D_{j} \bullet x^{52-4n},$$

FIG. 14D


590a
590
WAVEFORM SHAPING CIRCUIT
AGC
LEVEL SLICER FIRST SLICE LEVEL
591
DEMODULATOR
EFM
592
36
ECC DECODER
HPF
OPTICAL PLAYBACK SIGNAL
38a
CLOCK REGENERATOR
SUBCODE SIGNAL
596
600
LOW-REFLECTIVITY POSITION DETECTOR
DEMODULATED CLOCK
MARK SIGNAL DETECTOR (PHYSICAL ADDRESS OUTPUT SECTION)
593
LOW-REFLECTIVITY PORTION ADDRESS/CLOCK NUMBER POSITION SIGNAL OUTPUT SECTION
597
599
LOW-REFLECTIVITY PORTION ADDRESS/CLOCK NUMBER POSITION SIGNAL
LOW-REFLECTIVITY LIGHT AMOUNT DETECTOR
586
ADDRESS OUTPUT SECTION
594
n-1 ADDRESS OUTPUT SECTION
LOW-REFLE-CTIVITY PORTION START/END POSITION DETECTOR
LIGHT AMOUNT LEVEL COMPARATOR (LEVEL SLICER)
587
SYNCHRONIZING SIGNAL OUTPUT SECTION
SYNC
DATA CLOCK
598
SYNC COUNTER
595
598b
CLOCK COUNTER
598a
LIGHT AMOUNT REFERENCE VALUE
588
SECOND SLICE LEVEL
LOW-REFLECTIVITY PORITON DETECTION SIGNAL
TIME DELAY CORRECTOR
607
REFERENCE DELAY TIME TO MEASURING SECTION
608
CIRCUIT DELAY TIME STORING SECTION
608a
800
829
LPF
943
ROTATION CONTROLLER
26
17
MOTOR
SENSOR
17a
928
COMPARING MEANS
MOTOR ROTATION PULSE
CAV ROTATIONAL SPEED CONTROL
26a
26b
829
942
PE-RZ DEMODULATOR
ECC DECODER
DEINTER-LEAVER
RS DECODER
CIPHER DECODER
534
OPTICAL RECORDING SIGNAL
CLV ROTATION PHASE CONTROL
928a
928b
CPU
ID NUMBER OUTPUT SECTION
750
828
FOCUS DRIVER
1ST LAYER/2ND LAYER SWITCHING SECTION
827

FIG. 15


MARK NUMBER - 1
COPY PROTECTION BY PINCUSHION
(1) CROSS SECTION OF OPTICAL DISK
(2) REFLECTED LIGHT SIGNAL
REFERENCE LIGHT AMOUNT LEVEL
t
(3) ENVELOPE
(4) REPRODUCED SIGNAL
101001001001
00100100100
(5) LOW-REFLECTIVITY LIGHT DETECTION SIGNAL
NON REFLECTING SIGNAL
(6) CLOCK SIGNAL
1T
TRACK NO. TO
PREDICT
604
(7) ADDRESS NUMBER AND CLOCK NUMBER REFERENCE SIGNAL
ADDRESS An-1
ADDRESS An
FRAME SYNC
S1
m+1
m+2
m+3
m+4
m+256
m+257
ADDRESS n+1
603
605
606
TD
REFERENCE DELAY TIME
REFERENCE CLOCK
(TRACK NO. TO + 1)
(8) NEXT TRACK SIGNAL ON LEGITIMATE DISK
ADDRESS An+11
ADDRESS An+12
SYNC
S2
m+13
m+14
m+15
m+267
603a
604a
605a
606a
DIFFERENCE
(TRACK NO. TO + 1)
(9) NEXT TRACK SIGNAL ON ILLEGALLY DUPLICATED DISK
m+20
m+21
m+22
m+277
603b
605b
606b

FIG. 16

LEGITIMATE DISK

LOW-REFLECTIVITY PORTION ADDRESS TABLE

609

MARK NO.	START POSITION ADDRESS	START POSITION SYNC NO	START POSITION CLOCK NUMBER	END POSITION ADDRESS	END POSITION SYNC NO	END POSITION CLOCK NUMBER
1	A n	S1	m+2	n		m+257
1	A n+12	S2	m+14	n+12		m+267
1	A n+23		m+25	n+23		m+300
...	...		...	...		...
2	A n+1		m+15	n+1		m+160
2	A n+13		m+85	n+13		m+250
2	A n+24		m+68	n+24		m+210
0	A n+9					
0						

← PLANNING →

ILLEGALLY DUPLICATED DISK

LOW-REFLECTIVITY PORTION ADDRESS TABLE

MARK NO.	START POSITION ADDRESS	START POSITION SYNC NO	START POSITION CLOCK NUMBER	END POSITION ADDRESS	END POSITION SYNC NO	END POSITION CLOCK NUMBER
1	n	S1	m+2	n		m+257
1	n+12	S2	m+21	n+12		m+277
1	n+22		m+4	n+22		m+230
...	...		...	...		...
2	n+1		m+36	n+1		m+190
2	n+13		m+120	n+13		m+281
2	n+25			n+25		
0	n+9					
0						

FIG. 17


PRODUCE MARK WITH RANDOMLY DROPPED PORTIONS ON REFLECTIVE FILM
735a
MEASUREMENT OF POSITION INFORMATION
735b
MEASURE MARK POSITION INFORMATION
735d
COMPRESS
735e
OBTAIN COMPRESSED, ECC-CODED POSITION INFORMATION H(M)
MESSAGE RECOVERY TYPE ENCRYPTION (SIGNATURE) OF POSITION INFORMATION
695g
SET SECRET KEYS d (512 or 1024 bits), p, q, 695b
695b
ENCRYPTION (SIGNATURE COMPUTATION) OF POSITION INFORMATION BY RSA FUNCTION, A MESSAGE RECOVERY TYPE FUNCTION
CIPHERTEXT: C=M^d mod n
695d
RECORD CIPHERTEXT C ON DISK
695
735k
SHIP DISK
698
735m
LOAD DISK
ENCRYPTION SIGNATURE VERIFICATION OF CIPHERTEXT
698e
RECOVER CIPHERTEXT
698f
SET PUBLIC KEYS e,n
e: 3 OR LARGER INTEGER
n: 512 OR 1024 BITS
698b
ENCRYPTION (SIGNATURE VERIFICATION)
698g
ERROR CHECK
NO
STOP
YES
735w
DISK CHECK ROUTINE

FIG. 18A


A
735w
DISK CHECK ROUTINE
EXPAND H
736a
OUTPUT POSITION INFORMATION
736b
MEASURE MARK POSITION INFORMATION ON DISK
736c
COMPARE OUTPUT POSITION INFORMATION WITH MEASURED POSITION INFORMATION
736d
736e
CHECK OK?
NO
736f
DISPLAY AS DUPLICATED DISK
YES
STOP
736g
EXECUTE PROGRAM OR OUTPUT DATA
736h

FIG. 18B


PROGRAM IN REPRODUCTION APPARATUS FOR DETECTING OPTICAL MARK WITH INCREASED ACCURACY OR STABILITY
REPRODUCE STRIPES, PE-RZ DEMODULATE REPRODUCED STRIPES AND OBTAIN CIPHERTEXT
865w
YES
ROUTINE FOR CONSTRUCTING POSITION INFORMATION TABLE
865a
RECOVER ENCRYPTED POSITION INFORMATION
865b
DECRYPTION OR SIGNATURE VERIFICATION
865c
CONSTRUCT POSITION INFORMATION TABLE (OPTICAL MARK NUMBER: m, ADDRESS: nm, START/END FRAME SYNC NUMBER, CLOCK NUMBER: Tsm, Tem
ROUTINE FOR MEASURING CIRCUIT DELAY TIME TD
865d
DETECT ADDRESS: ns-1
READ CIRCUIT DELAY TIME FROM ROM
865h
COUNT FRAME SYNC NUMBER AND CLOCK
865y
865f
REFERENCE NONREFLECTIVE SIGNAL DETECTED?
NO
YES
MEASURE AND STORE CIRCUIT DELAY TIME : TD
865g
865x
m = 0
865z
m = m + 1
ROUTINE FOR DETECTING ADDRESS AND CLOCK COUNT FOR OPTICAL MARK m
865i
DETECT ADDRESS: nm-1
COUNT FRAME SYNC NUMBER AND CLOCK
865j
865k
NONREFLECTIVE SIGNAL DETECTED?
NO
NEXT ADDRESS SIGNAL DETECTED?
NO
YES
YES
MEASURE START FRAME SYNC NUMBER CLOCK COUNT TSM AND END CLOCK COUNT TME
865m
ROUTINE FOR DETECTING PIRATED DISK
CORRECT CIRCUIT DELAY TIME TD
Tsm - TD = Ts'm
TEm - TD = TE'm
865n
READ TOLERANCE 866, tA AND PASS COUNT. ERROR DETECTION COUNT ALLOWABLE LIMT: NA,
865p
CHECK IF POSITION INFORMATION IS WITHIN TOLERANCE
tsm - tA < Ts'm < Tsm + tA
tEm - tA < TE'm < TEm + tA
865q
865r
OK ?
NO
YES
865s
CHECKED MARK COUNT=PASS COUNT?
NO
YES
ERROR DETECTION COUNT < NA?
YES
865t
NO
JUDGE AS LEGITIMATE DISK
865u
JUDGE AS ILLEGAL DISK
865v
RUN
STOP

FIG. 19


FIRST LAYER MARKING SIGNAL DETECTION WAVEFORM
(1) FIRST LAYER MARKING DETECTION SIGNAL
10 MM OR LONGER BLANK
MARKING
NO. m
1 MM OR LONGER BLANK
NEXT MARKING
m+1
t
NOTE: REGARDED AS
START POINT
END POINT
30 μ m MAX.=226 CLOCKS
(2) ADDRESS
ADDRESS (n)
ADDRESS (n+1)
(3) FRAME POSITION
FRAME 0
FRAME 1
FRAME 2
FRAME 3
FRAME 4
FRAME 25
0
1
2
3
4
5
25
0
(5) PLL REPRODUCTION CLOCK SIGNAL (1T=0.133 μ m)
01234
1364
HOLD VCO
MARK LAYER
TOLERANCE
PASS COUNT
50bit
2bit
3bit
1bit
4bit
18bit
5bit
11bit
8bit
(6) MARKING POSITION DATA
ATTRI BUTES
MARK NO. m
ADDRESS (SECTOR)
FRAME POSITION NUMBER
REPRODUCED CHANNEL CLOCK NUMBER
MARKING LENGTH (EFFECTIVE 6 BITS)
(7) DATA EXAMPLE
00 1BARS
01 2BARS
10 3BARS
11 4BARS
8 MAX.
30000 MAX. (HEX)
26 MAX. PER SECTOR
1365 CLOCKS MAX. PER FRAME
256 CLOCKS MAX. =8 BITS
ONE LAYER OR TWO
866
867

FIG. 20


SECOND LAYER MARKING SIGNAL DETECTION WAVEFORM
MARKING
NO. m
NEXT MARKING
m+1
10 MM OR LONGER BLANK
1 MM OR LONGER BLANK
(1) SECOND LAYER MARKING DETECTION SIGNAL
START POINT
END POINT
NOTE:
REGARDED AS
30 μ m MAX.= 226 CLOCKS
(2) SECOND ADDRESS
ADDRESS (n+10)
ADDRESS (n+11)
(3) FRAME POSITION
FRAME 0
FRAME 1
FRAME 2
FRAME 8
FRAME 9
FRAME 25
(4) FRAME SYNCHRONIZING SIGNAL
0
1
2
3
7
8
25
0
(5) PLL REPRODUCTION CLOCK SIGNAL (1T=0.133 μm)
05678
1364
HOLD VCO
t
MARK LAYER
46bit
2bit
3bit
1bit
18bit
5bit
11bit
8bit
ATTRI-BUTES
MARK m. MARK LAYER
ADDRESS (SECTOR)
FRAME POSITION NUMBER
REPRODUCED CHANNEL CLOCK NUMBER
MARKING LENGTH (EFFECTIVE 6 BITS)
(7) DATA EXAMPLE
00 1BARS
01 2BARS
10 3BARS
11 4BARS
8 MAX.
30000 MAX. (HEX)
26 MAX. PER SECTOR
1365 CLOCKS MAX. PER FRAME
256 CLOCKS MAX. = 8 BITS
ONE LAYER OR TWO LAYER

FIG. 21


INSTALLATION START
901a
SCRAMBLE IDENTIFIER=ON?
NO
YES
901b
SCRAMBLED?
NO
STOP
YES
CONNECT TO PERSONAL COMPUTER NETWORK
901c
INPUT USER ID, SOFTWARE ID
901d
901e
DRIVE ID EXISTS?
YES
901f
TRANSMIT DRIVE ID
NO
901h
DRIVE ID EXISTS?
NO
STOP
YES
TRANSMIT DISK ID
901i
COMPUTE PASSWORD WITH SUB PUBLIC KEY AND COMPARE WITH DRIVE ID
901k
YES
OK?
NO
STOP
COMPUTE PASSWORD WITH SUB PUBLIC KEY AND COMPARE WITH DISK ID
901m
OK?
NO
STOP
YES
RUN
901n
901b
SCRAMBLED?
NO
RUN
YES
STOP
PASSWORD ISSUING CENTER
PAYMENT RECEIVED?
901g
YES
GENERATE PASSWORD BY COMPUTING CIPHERTEXT OF DRIVE ID AND SOFTWARE ID USING SUB SECRET KEY
PAYMENT RECEIVED?
901j
YES
GENERATE PASSWORD BY COMPUTING CIPHERTEXT OF DISK ID AND SOFTWARE ID USING SUB SECRET KEY

FIG. 22


INPUT DATA
ID GENERATOR
908
ID NUMBER
INPUT SECTION
909
ECC ENCODER
907
ENCRYPTION ENCODER
830
RZ MODULATOR
910
LASER EMITTING CIRCUIT
911
(YAG) LASER
912
LASER POWER SUPPLY CIRCUIT
929
CONVERGING UNIT
914
803
802
801
800
MOTOR
915
ROTATION SENSOR
915a
ROTATION PULSE
CLOCK SIGNAL GENERATOR
913
MODULATING CLOCK

FIG. 23

FIG. 24A

FIG. 24B

FIG. 24C

FIG. 24D

FIG. 24E





FIG. 25A



FIG. 25B



FIG. 25C



FIG. 25D

FIG. 26A



FIG. 26B



FIG. 26C



FIG. 26D



FIG. 26E



(1) TOP PLAN VIEW



FIG. 27A



FIG. 27B



FIG. 28A



FIG. 28B



FIG. 29A



FIG. 29B



FIG. 30A

CONTROL DATA

1	2	3	4
STRIPE PRESENCE/ ABSENCE IDENTIFIER	STRIPE RECORDING CAPACITY	ADDITIONAL STRIPE DATA PRESENCE/ ABSENCE IDENTIFIER	STRIPE REVERSE-SIDE RECORD IDENTIFIER
937		939	948

FIG. 30B



FIG. 30C


START
930a
MOVE OPTICAL HEAD TO INNER PORTION
930b
ROTATIONAL SPEED CONTROL
930c
STRIPES PRESENT?
930i
NO
YES
PLAY BACK STRIPES
930d
COMPLETED?
930e
NO
YES
MOVE HEAD TO OUTER AREA
930f
ROTATION PHASE CONTROL
930g
PLAY BACK DATA
930h

FIG. 31


923
STRIPE AREA
944
STRIPE AREA
923a
923b
ADDRESS AREA
(PIT SIGNAL AREA)
ADDRESS AREA LENGTH > ONE PIT SIGNAL FRAME
t

FIG. 32

DATA STRUCTURE



FIG. 33A

DATA STRUCTURE WHEN n=1



FIG. 33B

RANDOM ERROR CORRECTION CAPABILITY

BIT ERROR RATE BEFORE CORRECTION	READ ERROR RATE AFTER CORRECTION
10^{-5}	1 IN 10^{10} DISKS
10^{-4}	1 IN 10^{7} DISKS
10^{-3}	1 IN 10^{4} DISKS
BURST ERROR CORRECTION CAPABILITY	

FIG. 33C

SYNCHRONIZATION CODE DATA

SYNCHRONIZATION CODE

SYNC BYTE /RESYNC	BIT PATTERN											
	FIXED PATTERN (CHANNEL BIT)								SYNC CODE (DATA BIT)			
	C_{15}	C_{14}	C_{13}	C_{12}	C_{11}	C_{10}	C_9	C_8	b_3	b_2	b_1	b_0
SB	0	1	0	0	0	1	1	0	0	0	0	0
RS_1	0	1	0	0	0	1	1	0	0	0	0	1
RS_2	0	1	0	0	0	1	1	0	0	0	1	0
⋮												
RS_i	0	1	0	0	0	1	1	0			i	
⋮												
RS_{15}	0	1	0	0	0	1	1	0	1	1	1	1

FIG. 34A



FIG. 34B

MAXIMUM CAPACITY

	RECORDING CAPACITY	TOTAL BYTE COUNT	EFFICIENCY	RECORDING AREA ANGLE	UNRECORDED AREA ANGLE
MINIMUM	12B	41B	29.3%	51 DEGREES	309 DEGREES
MAXIMUM	188B	271B	69.4%	336 DEGREES	24 DEGREES

FIG. 34C



FIG. 35A



FIG. 35B



FIG. 36A



FIG. 36B

FIG. 36C

FIG. 36D

(1) TIME SLOT

FIG. 37A

(2) CHANNEL BIT



FIG. 37B

(3) RECORDING PULSE



FIG. 37C

(4) EMITTING PULSE



FIG. 37D


DISK INSERTION OR PCA READ INSTRUCTION RECEIVED
MOVE OPTICAL HEAD TO OUTER AREA OF CONTROL DATA AREA
940n
PLAY BACK CONTROL DATA
940a
PCA STRIPE PRESENCE/ABSENCE IDENTIFIER = 1?
940b
NO
YES
REVERSE-SIDE RECORD IDENTIFIER = 0?
940h
NO
PLAY BACK RECORDING LAYER ON REVERSE SIFE OR OUTPUT "REVERSE-SIDE PLAYBACK INSTRUCTION"
940i
YES
SET TRACKING OFF AND MOVE OPTICAL HEAD TO INNER PORTION INWARD OF CONTROL DATA AREA
940c
SWITCH TO CAV ROTATIONAL SPEED CONTROL AND PLAY BACK PCA STRIPES
940d
COMPLETED?
NO
940e
YES
SWITCH TO ROTATION PHASE CONTROL AND MOVE OPTICAL HEAD TO OUTER PORTION
940f
SET TRACKING ON AND PLAY BACK DATA
940g

FIG. 38



FIG. 39B

FIG. 39A


START
MOVE OPTICAL HEAD TO INNER CIRCUMFERENCE OF CONTROL DATA AREA
947a
947n
TRACKING OK?
NO
SWITCH TRACKING MODE
947p
YES
ROTATION SPEED CONTROL(CAV)/PLAY BACK ADDRESS WITH TRACKING ON
947b
947c
CAN ADDRESS BE PLAYED BACK?
NO
947i
MOVE OPTICAL HEAD TO INNER CIRCUMFERENCE
YES
947e
ADJUST OPTICAL HEAD POSITION BASED ON ADDRESS FROM PCA EMPTY PORTION OF PCA AREA
PCA STRIPES PRESENT?
947q
NO
947r
READ PCA FLAG IN CONTROL DATA
YES
947f
PLAY BACK PCA STRIPES
947s
PCA FLAG PRESENT?
NO
COMPLETED?
947g
NO
YES
YES
SWITCH TO ROTATION PHASE CONTROL (CLV) AND MOVE OPTICAL HEAD TO OUTER PORTION
947h
READ PCA FLAG IN CONTROL DATA
947t
PCA FLAG PRESENT?
NO
947j
ERROR MESSAGE
947k
YES
CONTINUE
947m

FIG. 40


CONDITION OF to : 14T < to < t
(LARGER THAN SYNC 14T, SMALLER THAN BARCODE t)
956
t0 : STANDARD VALUE GENERATOR
to
954
COMPARING MEANS
Tmax < TR < to?
YES
TR
Tmax
955
MEMORY MEANS (T max)
TR
953
EDGE-SPACING MEASURING MEANS
957
CONTROLLER
800
WAVESHAPING
OSCILLATOR CLOCK
956
958
MOTOR DRIVE CIRCUIT

FIG. 41


954a
COMPARING MEANS
TR < Tmin?
YES
STROBE PULSE GENERATION
TR
Tmin
955a
MEMORY MEANS (T min)
959
BARCODE READING MEANS
TR
RESET SIGNAL
953
EDGE-SPACING MEASURING MEANS
957
CONTROLLER
800
WAVESHAPING
OSCILLATOR CLOCK
956
958
MOTOR DRIVE CIRCUIT

FIG. 42


966
FIRST OSCILLATOR
961
SYNCHRONIZATION SIGNAL EXTRACTING MEANS
960
CLOCK EXTRACTING MEANS (PLL)
fs
f1
964
MOVING MEANS
FIRST FREQUENCY COMPARATOR
965
WAVE SHAPING
957
CONTROLLER
800
962
PU POSITION SENSOR
958
MOTOR DRIVE CIRCUIT
ROTATIONAL PHASE CONTROL
B
A
ROTATIONAL SPEED CONTROL
963
969
fm
967
SECOND FREQUENCY COMPARATOR
f2
SECOND OSCILLATOR
968

FIG. 43


MARKING
9103
9102
9104
BARCODE OF
MARKING POSITION
INFORMATION
MARKING
READING
MEANS
9106
POSITION
INFORMATION
READING MEANS
9101
DECRYPTING
MEANS
9105
9107
COMPARING/
JUDGING MEANS
MATCH?
NO
YES
9109
REPRODUCTION
STOP SIGNAL
REPRODUCTION SIGNAL
9108

FIG. 44


PUBLIC KEY
PAIRED
SECRET KEY
CONTENTS PROVIDER (SOFTWARE COMPANY)
4502
ID GENERATOR
ID
4508
ENCRYPTION ENCODER
4503
ID SIGNATURE
4504
ID
4505
4501
ID
ID SIGNATURE
0001
αβγ • • •
PRESS FACTORY
PCA WRITER
4507
4506
PIT AREA
4509
PLAYER
4511
VERIFICATION SECTION
NO
STOP
OK
OPERATION
4510
ENCRYPTION DECODER
PUBLIC KEY
4506
PIT AREA

FIG. 45


SYSTEM OPERATOR
ENCRYPTION KEY (SECRET KEY)
4612
ID NUMBER
ENCRYPTION KEY (PUBLIC KEY)
001
2B6A26EF
512bit
002
003
04
4610
PAIRED
4611
COMMUNICATION SOFTWARE
ENCRYPTION DECODER
SECRET KEY
USER DATA VERIFICATION SECTION
CREDIT CARD NUMBER
SECRET KEY FOR EACH ID NUMBER
CIPHERTEXT ID
PLAINTEXT
PASSWORD
4620
USER'S PERSONAL COMPUTER
4606
COMMUNICATION SOFTWARE
ENCRYPTION ENCODER
PUBLIC KEY
USER CREDIT CARD NUMBER
PUBLIC KEY
4604
4601
4602
PRESS FACTORY
ENCRYPTION KEY TABLE
ID NUMBER
ENCRYPTION KEY (PUBLIC KEY)
001
1A1F2EF6
512bit
002
003
04
ID + PUBLIC KEY
4603
PCA WRITER
4604
4605

FIG. 46


TRACK PITCH
0.74 μm
803
802
815
825
801
862
FIRST LAYER
SECOND LAYER
RECORDING PIT
RECORDING PIT

FIG. 47



S0	S1	CONTROL SIGNAL	ADDRESS SIGNAL	PROGRAM NUMBER	INDEX	PROGRAM			0	TOTAL			ERROR CORRECTING CODE CRCC
						MINUTE	SECOND	SCC		MINUTE	SECOND	SCC	

FIG. 48